



83-A1043-0006



series: GLADIATOR SL I Accu Workplace luminaires

Type of installation: portable
 Type of Protection: IP 66
 Protection class: III
 Lamp: LED
 Dimensions: L 283, B 272, H 104
 Colour: black

Mobile, mains-independent battery-operated work light. Impact-resistant and break-proof 2-component plastic housing. Edge protection and handle with soft plastic (thermoplastic elastomer - TPE). Cover opal, made of impact- and break-resistant plastic (polycarbonate). Beam angle adjustable with handle, plastic (ABS). Ergonomically placed control panel with buttons for on/off and dimming in steps of 5, 10, 20, 50 and 100% and LED display of battery capacity and operating time. Modern Li-Ion battery with 27 Wh for up to 10 hours of operation. Includes plug-in power supply for charging (3.5 h) or mains operation with a 5 m supply cable.

accessories

- 95-0290-0006 Transport bag for work light blue
- 95-0170-0001 Tripod Standard, without castors, set with mounting rail for 1 work light zinc plated
- 95-0171-0001 Tripod Standard, with castors, set with mounting rail for 1 work light zinc plated
- 95-0172-0001 Tripod Standard, without castors, set with mounting rail for 2 work lights zinc plated
- 95-0173-0001 Tripod Standard, with castors, set with mounting rail for 2 work lights zinc plated
- 95-0270-0001 Magnet set, for attachment to the threaded bushes in the handle black

electro-technics:

Electric Gear Converter
 Voltage 220 - 240 V / 50 - 60 Hz
 System Power 36 W

Spezifikationen:

Colour TPE blue
 Colour handle black
 Power supply cable H05RN-F
 Size power supply cable 2 x 1,0 mm²
 Length power supply cable 5 m
 Colour power supply cable black
 Lamp cover opal

testings:

Type of Protection IP 66
 Protection class III
 Filament test 850°C - 30 seconds
 Impact resistance IK07 (2 Joule)
 Safety Marks D-mark
 Other Marks WEEE mark
 Country Code CE

lamp 1:

Colour rendering index (CRI) 80
 Colour Temperature 5000 K
 Number of Lamps 1
 Lamp LED
 Wattage 26,00 W
 Socket without socket
 Lifespan

weights and measures:

Length L 283 mm
 Width B 272 mm
 Height H 104 mm
 Weight 2,4 kg

lighting technology:

Luminaire flux 4.000 lm