

68A301B0-0062

series: Tube lights Tube lights

Type of installation:	Universal mounting system
Type of Protection:	IP 54
Protection class:	I
Lamp:	LED
Dimensions:	D 120, L 1030
Colour:	grey

Protective tube plastic opal (polycarbonate), end caps plastic grey (polyamide), integrated electronic driver, 2 protectors blue, socket, power supply cable with mains plug, incl. LED panel

electro-technics:

Electric Gear	Converter
System Power	33 W
Voltage	220 - 240 V / 0 Hz, 50 - 60 Hz

Spezifikationen:

Colour TPE	blue
Power supply cable	H07RN-F
Size power supply cable	3 x 1,5 mm²
Length power supply cable	5 m
Colour power supply cable	black
Connector systems	Typ E (CEE 7/5)
Socket outlets	1
Lamp cover	opal

testings:

Type of Protection	IP 54
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK08 (5 Joule)
Safety Marks	F-mark
Other Marks	WEEE mark

lamp 1:

Lamp	LED
Number of Lamps	3
Wattage	14,00 W
Socket	without socket
Colour Temperature	5000 K
Colour rendering index (CRI)	80
Lifespan	50000 h (L70/B50)

weights and measures:

Length L	1.030 mm
Diameter D	120 mm
Weight	3,1 kg

lighting technology:

Luminaire flux	3.900 lm

accessories

68Z00001	Mounting bracket (plastic) grey
68Z00002	Mounting bracket (metal) with magnet zinc plated
68Z00003	Mounting bracket (plastic) with magnet grey
68Z00007	Magnetic holder, mounting bracket (plastic) with rubberised magnet, set (2 pieces) zinc plated
68Z00004	Mounting bracket (metal) with hanger assembly of stainless steel zinc plated
68Z00016	Mounting bracket (plastic) with with key ring, rotatable luminaire, set (2 pcs.) grey
68Z00006	Mounting bracket (metal) with expander suspension (L 600 mm), set (2 pcs.) zinc plated
68Z00017	Mounting bracket (plastic) with expander suspension (L 600 mm), rotatable luminaire, set (2 pcs.) grey
68Z00005	Mounting bracket (metal) with adjustable belt suspension (L 330-550 mm), set (2 pcs.) zinc plated
68Z00008	Mounting bracket (plastic) with adjustable belt suspension (L 330-550 mm), rotatable luminaire, set (2 pcs.) grey