



# 70-2000-0006

series: BEAM Workplace luminaires



Type of installation: portable  
Type of Protection: IP 65  
Protection class: II  
Lamp: LED  
Dimensions: L 352, B 223, H 357  
Colour: blue

Housing plastic (polycarbonate, edge guard made of soft thermoplastic elastomer TPE), cover plastic opal (polycarbonate), retractable stainless steel mounting hook with safeguard, second cable entry optional (through-wiring option), 3 m power supply cable with mains plug

## electro-technics:

Electric Gear Converter  
System Power 47 W  
Voltage 220 - 240 V / 50 - 60 Hz

## Spezifikationen:

Colour handle black  
Power supply cable H07RN-F  
Size power supply cable 2 x 1,0 mm<sup>2</sup>  
Length power supply cable 3 m  
Colour power supply cable black  
Connector systems E+F, Konturenst. (CEE 7/17)  
Lamp cover opal

## testings:

Type of Protection IP 65  
Protection class II  
Filament test 850°C - 30 seconds  
Impact resistance IK06 (1 Joule)  
Safety Marks D-mark  
Other Marks WEEE mark  
Country Code nicht verwenden!

## lamp 1:

Lamp LED  
Number of Lamps 1  
Wattage 43,00 W  
Socket without socket  
Colour Temperature 5000 K  
Colour rendering index (CRI) 80  
Lifespan 30000 h

## weights and measures:

Length L 352 mm  
Width B 223 mm  
Height H 357 mm  
Weight 1,838 kg

## lighting technology:

Luminaire flux 4.500 lm